



# KING CEILING 1500lm

## Bulkhead 1500lm 15W CCT 3000/4000K IP66 IK10

**Model No.:** LUKIN01  
**SGSO Sku:** 0028920010  
**GTIN/EAN:** 7630268401788

Suitable for wall mounting:	Yes
Suitable for ceiling mounting:	Yes
Suitable for surface mounting:	Yes
Lamp type:	LED not exchangeable
With light source:	Yes
Suitable for number of lamps:	1
Lamp holder:	Other
Material housing:	Plastic
Colour housing:	White
Material cover:	Plastic, opal
Voltage type:	AC
Nominal voltage:	220 ... 240 V
Nominal current:	70 mA
Type of control gear:	LED operating device current-
With control gear:	yes
No dim function:	Yes
Light distributor:	Diffuser lens/optic/panel
Light sharing:	Symmetric
Beam angle:	Open beam/diffuse
Colour consistency (McAdam ellipse):	SDCM4
Energy efficiency class of the built-in lamp:	Other
Rated life time L70/B50 at 25 °C:	50000 h
Rated life time L80/B10 at 25 °C:	40000 h
Rated life time L90/B10 at 25 °C:	30000 h
Degree of protection (IP):	IP66
Impact strength:	IK10
Protection class:	II
Rated ambient temperature according to IEC62722-2-1:	-20 ... 45 °C
Filament test according to IEC 60695-2-11:	750 °C - 30 s
Suitable for lamp power:	15 W
Max. system power:	15 W
Luminaire efficacy:	100 lm/W
Rated luminous flux according to IEC 62722-2-1:	1500 lm
Colour of light:	White
Colour temperature:	3000 ... 4000 K
Colour rendering index CRI:	80-89
Power factor:	0.9
Height/depth:	98 mm
Outer diameter:	308 mm
Unified Glare Ratio (UGR):	28

